

## Specifications

Product name	LCD color TV			
Model name	LC-32P1-W	LC-26P1-W	LC-22P1-W	
Color	White			
Screen size	32V-inch (69.8 H x 39.3 V cm; 80.1 cm on the diagonal)	26V-inch (56.5 H x 31.8 V cm; 64.8 cm on the diagonal)	22V-inch (47.6 H x 26.8 V cm; 54.6 cm on the diagonal)	
Drive system	TFT (thin-film transistor) active-matrix drive			
Dot count	1,920 H x 1,080 V pixels			
LCD panel	Screen brightness	400 cd/m <sup>2</sup>		
	Contrast	2000:1	1500:1	
	Viewing angle	Vertical: 176°, horizontal 176°		
	Backlight source	Internal (built-in fluorescent tube)		
Speakers	3.0 cm x 10.0 cm x 2, 2.0-cm diameter x 2			
Max. audio output (JEITA)	Total 10.0 W (5.0 W + 5.0 W)			
AC power supply voltage	100 V AC, 50/60 Hz			
Power consumption	160 W	124 W	100 W	
Standby power consumption	0.13 W	0.13 W	0.12 W	
Annual power consumption* <sup>3</sup>	146 kWh/year	112 kWh/year	91 kWh/year	
Main unit dimen-sions	Display section only	80.3 W x 8.96 D x 51.2 H cm	66.8 W x 8.96 D x 43.9 H cm	57.0 W x 9.99 D x 37.8 H cm
	With table stand	80.3 W x 27.9 D x 58.2 H cm	66.8 W x 27.9 D x 50.9 H cm	57.0 W x 27.1 D x 44.8 H cm
Main unit weights	Display section only	Approx. 15.5 kg	Approx. 13.0 kg	Approx. 7.6 kg
	With table stand	Approx. 18.5 kg	Approx. 15.5 kg	Approx. 9.7 kg
TV reception channels	VHF channels 1 to 12 UHF channels 13 to 62 Cable TV channels 13 to 63 Digital BS channels 001 to 999 Digital CS110° channels 000 to 999 Digital terrestrial channels 011 to 528 (with cable TV pass-thru)			
Input/output jacks	Video input (2 sets) S2 video input D5 video input			

HDMI input (2 sets)\*<sup>4</sup>  
 Digital PC input (DVI-D input, with audio input jack)  
 Analog PC input (mini D-sub 15-pin, with audio input jack)  
 Monitor output (combined with S2 jack, doubles as video input and  
 recording output jack)  
 Headphone output  
 Digital audio output (optical)  
 i.LINK (TS) S400 (2 sets)  
 B-CAS card slot  
 VHF/UHF antenna input  
 BS/CS110° antenna input  
 Telephone line (2,400 bps)  
 LAN (10Base-T/100Base-TX)  
 RS232C  
 AC power input

Accessories

Table stand (assembled with main unit)  
 AC power cord  
 Wireless remote control  
 AAA dry cell battery  
 B-CAS card  
 VHF/UHF antenna cable  
 Telephone cable  
 Modular splitter  
 Tipover-prevention hardware (1 set)  
 Cable clamp  
 Cable cover  
 Operation manual  
 Easy user's guide  
 Warranty card

\*3 Measured with AV position in "Standard."

\*4 Supports 480i, 480p, 1080i, 720p, and 1080p.